

tesa® extra Power Perfect



56339 / 56341 / 56342 / 56343 / 56344

Product Information

tesa® extra Power Perfect is a powerful high quality acrylic coated cloth tape. It is based on a 145 mesh woven rayon fabric backing and a natural rubber adhesive. It has a high adhesion even on rough surfaces and an excellent tensile strength.

Main Application

- For all professional solutions like handicrafts, fastening, bundling, strengthening and marking
- For permanently high resilience and long-term results
- Very strong and perfect adhesive power, also on rough surfaces
- Tear-resistant but tearable by hand
- Can be written on
- Straight tear edges longitudinal and horizontal
- Wide range of colors
- Formable

Technical information (average values)

The values in this section should be considered as average figures or typical only and should not be used for specification purposes.

Technical Data

• Backing material	Acrylic-coated cloth	• Elongation at break	13%
• Total thickness	310 µm	• Tensile strength	100 N/cm
• Type of adhesive	Natural rubber	• Mesh	145 count per m ²
		• Temperature resistance (30min)	130 °C

Adhesion to

- | | |
|---------|----------|
| • steel | 3.3 N/cm |
|---------|----------|

Properties

- | | | | |
|----------------------------|------|-----------------------|------|
| • Hand tearability | ●●●● | • Abrasion resistance | ●●●● |
| • Straight tear edges | ●●●● | • Water resistance | ●●● |
| • Suitable for die cutting | yes | | |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

tesa® extra Power Perfect



56339 / 56341 / 56342 / 56343 / 56344

Product Information

Additional Information & Pictures



56339, 56341, 56342, 56343, 56344

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.