



Ground warning sign  
Ref. 7010-18



**Product description**

Ground warning signs for marking the location of fire extinguishers within the workplace to ensure access is maintained at all times. High quality adhesive suitable for use on all flat, clean surfaces indoor (excluding carpet), and will function perfectly in temperatures ranging from -20°C to +60°C. Semi-matt and antiskid surface certified according to DIN standards 51097 (grade A) and DIN 51130 (grade R9). The non-reflective coating ensures optimum readability. Flexible and resistant adhesive PVC. Positioning advice on reverse of sticker. Dim. 700 x 350 mm Thickness 0.2 mm, will not damage or peel off if a fork-lift truck is driven over it.

! During the installation of these stickers it is recommended to inform staff of their significance because it is everyone's duty to take care of their security at the workplace.

High quality materials	Complies with all known safety standards	Easy fitting process
<p>High performance adhesive for optimum adherence</p> <p>Non-reflective coating for optimum readability even in direct lighting</p> <p>Very thin to prevent tripping hazard and damage from the frequent passage of fork lift trucks, etc.</p>	<p>Pictograms complying with standards and perfectly understandable for everyone</p> <p>R9</p> <p>A</p> <p>Antiskid</p> <p>Non-flammable</p>	<p>Half-moon shape for easy fitting</p> <p>Instruction video:</p> <p>Economical and simple can be applied in 1 min</p> <p>Dimensions 700x350 Thk.0,2 mm</p> <p>Clean, stain free removal possible</p>

Positioning advice:	
<ul style="list-style-type: none"> <li>Minimum application temperature: + 10°C.</li> <li>Carefully clean the surface where the sticker will be placed: it must be free of dust, degreased and completely dry.</li> <li>Remove the protective film from the adhesive sticker.</li> <li>Apply the sticker in the desired location (taking into account alignment with the area to be highlighted).</li> <li>Press down from the inside of the sticker to the outside (to remove air bubbles).</li> </ul>	<ul style="list-style-type: none"> <li>It is forbidden to walk on the sticker during the first 24 hours of placement, in order that the adhesive sticks perfectly to the surface.</li> </ul>
To remove	
<ul style="list-style-type: none"> <li>Heat the sticker to facilitate removal (for example: with a hair dryer) then use a scraper.</li> <li>Carefully clean the surface with a solvent to remove any remaining adhesive residue.</li> </ul>	

**Available colours**

Ref.	Product Code	UoS Barcode	Inner box Barcode	Outer box Barcode	Pallet Barcode
7010-18	1701080151	3462159009186	3462159009193	NC	3462159009209

**Intrastat code**

3919908099

**Logistics data**

Ref.	UoS			Inner Box			Outer Box				Pallet			
	Dimensions mm	Unit weight Kg	Pack Qty	Dimensions mm	Gross weight kg	Unit weight kg	Pack Qty	Dimensions mm	Gross weight kg	Unit weight kg	Pack Qty	Dimensions mm	Gross weight kg	Unit weight kg
7010-18	700 x 350 H 0,2	0,095	10	715 x 360 H 14	1,19	0,95	NC	NC	NC	NC	900	1200 x 800 H 545	117	86



Preserve easy access to any fire-fighting equipment installed in the workplace

The **Regulatory Reform** (Fire Safety) Order 2005 says that the responsible person as well as everyone in the workplace must make sure that:

Any non-automatic fire-fighting equipment provided is easily accessible, simple to use and indicated by signs. (Article 13)